



B'laster PB Penetrating Lithium Grease

SAFETY DATA SHEET

OSHA HCS (29 CFR 1910.1200)

SECTION 1: PRODUCT AND COMPANY IDENTIFICATION

Product identifier

Chemical Name	Mixture
CAS No.	Mixture
Trade Name	B'laster PB Penetrating Lithium Grease
Product Code	GR-8A-PB

Relevant identified uses of the substance or mixture and uses advised against

Identified Use(s)	Lubricant
Uses Advised Against	None

Company Identification	B'laster Corporation 8500 Sweet Valeey Drive Valley View, OH 44125
Telephone	(800) 858-6605 / (216) 901-5800
Fax	(216) 901-5801
Website	www.blastercorp.com

Emergency telephone number

Emergency Phone No.	ChemTel: (800) 255-3924 Transportation Emergency: ChemTel: (800) 255-3924
---------------------	---

SECTION 2: HAZARDS IDENTIFICATION

Classification of the substance or mixture

OSHA HCS (29 CFR 1910.1200)

Flam. Aerosol 2; Liquefied gas; Skin Irrit. 2; Eye Irrit. 2; STOT SE 3; Asp. Tox. 1

Label elements

Hazard Symbol



DANGER

Signal word(s)

Hazard Statement(s)

Flammable aerosol.
Contains gas under pressure; may explode if heated.
Causes skin irritation.
Causes serious eye irritation.
May cause drowsiness or dizziness.
May be fatal if swallowed and enters airways.

Precautionary Statement(s)

Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
Do not spray on an open flame or other ignition source.
Do not pierce or burn, even after use.
Wear protective gloves/protective clothing/eye protection/face protection.
Wash hands and exposed skin after use.
Avoid breathing spray.
Use only outdoors or in a well-ventilated area.
Protect from sunlight and do not expose to temperatures exceeding 50 °C/122 °F.



B'laster PB Penetrating Lithium Grease

Other hazards

Toxic to aquatic life. Toxic to aquatic life with long lasting effects.

SECTION 3: COMPOSITION/INFORMATION ON INGREDIENTS

Hazardous Ingredient(s)	% wt.	CAS No.	Hazard classification
Distillates (petroleum), hydrotreated light	30 - 40	64742-47-8	Skin Irrit. 2; H315 STOT SE 3; H336 Asp. Tox. 1; H304 Flam. Liq. 4; H227 Aquatic Acute 2; H401 Aquatic Chronic 2; H411
Distillates (petroleum), hydrotreated heavy naphthenic	5 - 15	64742-52-5	Asp. Tox. 1; H304
Solvent Naptha (Petroleum) Heavy Aromatic	5 - 15	64742-94-5	Flam. Liq. 4; H227 STOT SE 3; H336 Asp. Tox. 1; H304 Aquatic Acute 2; H401 Aquatic Chronic 2; H411
Propane	5 - 10	74-98-6	Flam. Gas 1; H220 Liquefied gas; H280
n-Butane	5 - 10	106-97-8	Flam. Gas 1; H220 Liquefied gas; H280
Dinonylphenol, ethoxylated, phosphated	0.1 - 2	39464-64-7	Skin Irrit. 2; H315 Eye Dam. 1; H318 Aquatic Acute 3; H402 Aquatic Chronic 4; H413
Naphthalenesulfonic acid, dinonyl-, calcium salt (2:1)	< 1	57855-77-3	Skin Irrit. 2; H315 Eye Irrit. 2; H319
Zinc oxide	< 1	1314-13-2	Aquatic Acute 1; H400 Aquatic Chronic 1; H410
Lubricating oils (petroleum), hydrotreated spent	< 1	64742-58-1	Not classified as dangerous for supply/use.

Additional Information – None

* The exact percentage withheld as a trade secret in accordance with 29 CFR 1910.1200.

SECTION 4: FIRST AID MEASURES



Description of first aid measures

Inhalation

Move person to fresh air. If breathing is laboured, administer oxygen. If symptoms develop, obtain medical attention.

Skin Contact

Wash affected skin with soap and water. If symptoms develop, obtain medical attention. Take off contaminated clothing and wash it before reuse.

Eye Contact

Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists, get medical advice/attention.

Ingestion

Immediately call a POISON CENTER or doctor/physician. Do not induce vomiting. Do not give anything by mouth to an unconscious person.

Most important symptoms and effects, both acute and delayed

Aspiration of droplets may cause pulmonary oedema.

B'laster PB Penetrating Lithium Grease

Indication of any immediate medical attention and special treatment needed

IF SWALLOWED: Immediately call a POISON CENTER or doctor/physician.

SECTION 5: FIRE-FIGHTING MEASURES

Extinguishing Media

- Suitable Extinguishing Media
- Unsuitable Extinguishing Media

Extinguish with carbon dioxide, dry chemical, foam or water spray. Do not use water jet.

Special hazards arising from the substance or mixture

Flammable vapor.

Advice for fire-fighters

A self contained breathing apparatus and suitable protective clothing should be worn in fire conditions. Keep containers cool by spraying with water if exposed to fire.

SECTION 6: ACCIDENTAL RELEASE MEASURES

Personal precautions, protective equipment and emergency procedures

Eliminate sources of ignition. Avoid contact with eyes. Avoid breathing spray. Wear protective gloves/eye protection.

Environmental precautions

Prevent liquid entering sewers, basements and work pits. Avoid release to the environment.

Methods and material for containment and cleaning up

Cover spills with inert absorbent material. Transfer to a container for disposal or recovery.

Reference to other sections Additional Information

None
None

SECTION 7: HANDLING AND STORAGE

Precautions for safe handling

Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Avoid contact with skin and eyes. Use product in a well-ventilated area only. Avoid breathing spray.

Conditions for safe storage, including any incompatibilities

-Storage temperature

Store in a well-ventilated place. Protect from sunlight. Do not expose to temperatures exceeding 50°C/ 122°F. Keep container tightly closed.

-Incompatible materials

This product should be stored away from sources of strong heat, strong acids, oxidizing chemicals and reducing agents.

Specific end use(s)

Lubricant

SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION

Occupational Exposure Limits

SUBSTANCE.	CAS No.	(8hr TWA)		(STEL)		Note:
		PEL (OSHA)	TLV (ACGIH)	PEL (OSHA)	TLV (ACGIH)	
Mineral oils / Oil Mist	-----	5 mg/m3	5 mg/m3 ⁽¹⁾	-----	-----	⁽¹⁾ Inhalable
Alkanes (C9-C15)	-----	-----	1200 mg/m3	-----	-----	-----
Propane	74-98-6	1000 ppm	Aspyx. [#]	-----	-----	#
n-Butane	106-97-8	-----	250 ppm	-----	-----	-----

[#]Assure minimum oxygen content of work atmosphere.

B'laster PB Penetrating Lithium Grease

Recommended monitoring method

NIOSH 1550 (Naphthas); NIOSH 5026 (Oil mist; mineral); NIOSH 1500 (hydrocarbons, B.P. 36 - 216 °C)

Exposure controls

Appropriate engineering controls

Ensure adequate ventilation.

Personal protection equipment

Eye/face protection

Wear protective eyewear (goggles, face shield, or safety glasses).



Skin protection (Hand protection/ Other)

Wear suitable gloves if prolonged skin contact is likely (Nitrile rubber or Butyl rubber). Check with protective equipment manufacturer's data.



Respiratory protection

Normally no personal respiratory protection is necessary. In case of insufficient ventilation, wear suitable respiratory equipment. Check with protective equipment manufacturer's data.



Thermal hazards

Not normally required. Use gloves with insulation for thermal protection, when needed.

Environmental Exposure Controls

Avoid release to the environment.

SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES

Information on basic physical and chemical properties

Appearance

Aerosol spray

Color.

Clear

Odor

Mild petroleum, Solvent-like.

Odor Threshold (ppm)

Not available

pH (Value)

Not available

Melting Point (°C) / Freezing Point (°C)

Not available.

Boiling point/boiling range (°C):

Not available.

Flash Point (°C)

-104 (Propane)

Evaporation Rate

Not available.

Flammability (solid, gas)

Extremely flammable

Explosive Limit Ranges

2.1% - 9.5% v/v (Propane)

Vapor pressure (Pascal)

ca. 95×10^4 (Propane)

Vapor Density (Air=1)

ca. 1.56 @ 0°C (Propane)

Density (g/ml)

Not available

Solubility (Water)

Not available

Solubility (Other)

Not available

Partition Coefficient (n-Octanol/water)

Not available

Auto Ignition Point (°C)

450 (Propane)

Decomposition Temperature (°C)

Not available

Kinematic Viscosity (cSt)

< 20.5 @ 40 °C

Explosive properties

Not explosive.

Oxidizing properties

Not oxidizing.

Other information

None

SECTION 10: STABILITY AND REACTIVITY

Reactivity

Stable under normal conditions.

Chemical stability

Stable.

B'laster PB Penetrating Lithium Grease

Possibility of hazardous reactions	None anticipated.
Conditions to avoid	Avoid contact with heat and ignition sources.
Incompatible materials	This product should be stored away from sources of strong heat , strong acids, oxidizing chemicals and reducing agents.
Hazardous decomposition product(s)	Carbon monoxide, Carbon dioxide, Metal oxides, Acid smoke

SECTION 11: TOXICOLOGICAL INFORMATION

Exposure routes: Inhalation, Skin Contact, Eye Contact

Information on toxicological effects

Distillates (petroleum), hydrotreated light (CAS No. 64742-47-8) - By analogy with similar materials:

Acute toxicity (calculated / estimated)	Oral: LD50 >5000 mg/kg-bw Dermal: LD50 >2000 mg/kg-bw Inhalation: LC0 ≥5.28 mg/l (Vapor), 4-hr. rat - May cause drowsiness or dizziness.
Irritation/Corrosivity	Causes skin irritation. Repeated exposure may cause skin dryness or cracking.
Sensitization	It is not a skin sensitizer.
Repeated dose toxicity	Oral: NOEL 750 mg/kg Dermal: NOEL 0.5 ml/kg bw Inhalation: NOEL ≥1000 mg/m3
Carcinogenicity	It is unlikely to present a carcinogenic hazard to man.

NTP	IARC	ACGIH	OSHA	NIOSH
No.	No.	No.	No.	No.

Mutagenicity	Not to be expected
Reproductive toxicity	Not to be expected

Solvent Naptha (Petroleum) Heavy Aromatic (CAS No. 64742-94-5)

Acute toxicity (calculated / estimated)	Oral: LD50 >5 g/kg-bw Dermal: LD50 >2 g/kg-bw Inhalation: LC50 >20 mg/l (Vapor), 4-hr. rat - May cause drowsiness or dizziness.
Irritation/Corrosivity	Causes serious eye irritation. Unlikely to cause skin irritation.
Sensitization	It is not a skin sensitizer.
Repeated dose toxicity	No data
Carcinogenicity	It is unlikely to present a carcinogenic hazard to man.

NTP	IARC	ACGIH	OSHA	NIOSH
No.	2B	No.	No.	No.

Mutagenicity	Not to be expected
Reproductive toxicity	Not to be expected

SECTION 12: ECOLOGICAL INFORMATION

Distillates (petroleum), hydrotreated light (CAS No. 64742-47-8) - By analogy with similar materials:

Ecotoxicity

Short term	LC50 (96 hour): 2.5 mg/L (fish) EC50 (48 hour): 1.4 mg/L (crustacea) EC50 (72 hour): 1.3 mg/L (algae)
------------	---

B'laster PB Penetrating Lithium Grease

Long Term	NOEC (28 days): 0.098 mg/L (fish) LOEC (21 days): 1.2 mg/L (crustacea) LOEL (72 hour): 1 mg/L (algae)
Persistence and degradability	Biodegradable
Bioaccumulative potential	The product has no potential for bioaccumulation.
Mobility in soil	Not available.
Results of PBT and vPvB assessment	Not classified as PBT or vPvB.
Other adverse effects	None known.

Solvent Naptha (Petroleum) Heavy Aromatic (CAS No. 64742-94-5)

Short term	LC50 (96 hour): 3 mg/L (<i>Oncorhynchus mykiss</i>) EL50 (48 hour): 1.1 mg/L (<i>Daphnia magna</i>)
Long Term	No data
Persistence and degradability	Part of the components are poorly biodegradable.
Bioaccumulative potential	The product has no potential for bioaccumulation.
Mobility in soil	Not available.
Results of PBT and vPvB assessment	Not classified as PBT or vPvB.
Other adverse effects	None known.

SECTION 13: DISPOSAL CONSIDERATIONS

Waste treatment methods	Disposal should be in accordance with local, state or national legislation. Consult an accredited waste disposal contractor or the local authority for advice.
-------------------------	--

SECTION 14: TRANSPORT INFORMATION

	<u>U.S. DOT</u>	<u>Sea transport (IMDG)</u>	<u>Air transport (ICAO/IATA)</u>
UN number	1950	1950	1950
Proper Shipping Name	Aerosols, flammable	Aerosols, flammable	Aerosols, flammable
Transport hazard class(es)	2.1	2.1	2.1
Packing group	Not applicable	Not applicable	Not applicable
Environmental hazards	None assigned	None assigned	None assigned
Special precautions for user	None assigned	None assigned	None assigned

Transport in bulk according to Annex II of MARPOL73/78 and the IBC Code: Not applicable

SECTION 15: REGULATORY INFORMATION

Safety, health and environmental regulations/legislation specific for the substance or mixture:

TSCA (Toxic Substance Control Act) - Inventory Status: All components listed or polymer exempt.

Designated Hazardous Substances and Reportable Quantities (40 CFR 302.4):

Chemical Name	CAS No.	Typical %wt.	RQ (Pounds)
None	----	----	----

SARA 311/312 - Hazard Categories:

☒ Fire ☒ Sudden Release ☐ Reactivity ☒ Immediate (acute) ☐ Chronic (delayed)

SARA 313 - Toxic Chemicals (40 CFR 372):

Chemical Name	CAS No.	Typical %wt.
Zinc compounds (Zinc oxide)	1314-13-2	< 2



B'laster PB Penetrating Lithium Grease

SARA 302 - Extremely Hazardous Substances(40 CFR 355):

Chemical Name	CAS No.	Typical %wt.	TPQ (pounds)
None	----	----	----

California Proposition 65 List:

Chemical Name	CAS No.	Typical %wt.	Type of Toxicity
Naphthalene	91-20-3	-----	Cancer

SECTION 16: OTHER INFORMATION

The following sections contain revisions or new statements: 1-16.

Date of preparation: June 20, 2017

Hazard Statement(s) and Risk Phrases Listed in: SECTION 2:/ SECTION 3:

Hazard Statement(s)

- H220: Extremely flammable gas.
- H227: Combustible liquid.
- H280: Contains gas under pressure; may explode if heated.
- H304: May be fatal if swallowed and enters airways.
- H315: Causes skin irritation.
- H318: Causes serious eye damage.
- H319: Causes serious eye irritation.
- H336: May cause drowsiness or dizziness.
- H400: Very toxic to aquatic life.
- H401: Toxic to aquatic life.
- H402: Harmful to aquatic life.
- H410: Very toxic to aquatic life with long lasting effects
- H411: Toxic to aquatic life with long lasting effects.
- H413: May cause long lasting harmful effects to aquatic life.

Training advice: None.

Disclaimer: We believe the statements, technical information and recommendations contained herein are reliable, but they are given without warranty or guarantee of any kind. The information contained in this document applies to this specific material as supplied. It may not be valid for this material if it is used in combination with any other materials. It is the user's responsibility to satisfy oneself as to the suitability and completeness of this information for the user's own particular use.